AWTA Product Testing

Australian Wool Testing Authority Ltd - trading as AWTA Product Testing A.B.N 43 006 014 106

1st Floor, 191 Racecourse Road, Flemington, Victoria 3031 P.O Box 240, North Melbourne, Victoria 3051 Phone (03) 9371 2400 Fax (03) 9371 2499

TEST REPORT

Client: Meganite Inc.

> 1461 South Balboa Ontario, California 91761

USA

19-006317 Test Number : **Issue Date** 20/11/2019

Print Date

29/11/2019

Sample Description

Clients Ref:

"Meganite Acrylic Solid Surface" ASNZS 1530.3-1999

Rigid Panel

Colour: White

End Use: Benchtop, Wall Cladding

Acrylic Resin (PMMA), ATH, Colourant Nominal Composition: Approx 2.3kg/m2 Nominal Mass per Unit Area/Density:

Nominal Thickness: 12mm

AS/NZS 1530.3-1999

Methods for Fire Tests on Building Materials, Components and Structures

Part 3: Simultaneous Determination of Ignitability, Flame Propagation, Heat Release and Smoke Release

Face tested: Face

Date tested: 20/11/2019

Standard Error Mean Ignition time 0.22 10.59 min Flame propagation time Nil Nil sec Heat release integral 1.6 24.2 kJ/m²

Smoke release, log d 0.0885 -2 0866

Optical density, d 0.0091 / metre

Number of specimens ignited: 6 Number of specimens tested: 6

Regulatory Indices:

Ignitability Index Range 0-20 Spread of Flame Index Range 0-10 Heat Evolved Index Range 0-10 Smoke Developed Index Range 0-10

187333 40122 Page 1 of 2

Australian Wool Testing Authority Ltd Copyright - All Rights Reserved



Accredited for compliance with ISO/IEC 17025 - Testing - Chemical Testing

Mechanical Testing

Performance & Approvals Testing

: Accreditation No

Accreditation No · Accreditation No. 1356

983



Samples and their identifying descriptions have been provided by the client unless otherwise stated. AWTA Ltd makes no warranty, implied or otherwise, as to the source of the tested samples. The above test results relate only to the sample or samples tested. This document shall not be reproduced except in full and shall be rendered void if amended or altered. This document, the names AWTA Product Testing and AWTA Ltd may be used in advertising providing the content and format of the advertisement have been approved by the Managing Director of AWTA Ltd.

A. JACKSON B.Sc.(Hons)

AWTA Product Testing

Australian Wool Testing Authority Ltd - trading as AWTA Product Testing A.B.N 43 006 014 106

1st Floor, 191 Racecourse Road, Flemington, Victoria 3031 P.O Box 240, North Melbourne, Victoria 3051 Phone (03) 9371 2400 Fax (03) 9371 2499

TEST REPORT

Client: Meganite Inc.

> 1461 South Balboa Ontario, California 91761

USA

19-006317 Test Number :

Issue Date

Print Date 29/11/2019

20/11/2019

These results only apply to the specimen mounted, as described in this report. The result of this fire test may be used to directly assess fire hazard, but it should be recognised that a single test method will not provide a full assessment of fire hazard under all fire conditions.

Each test specimen had an unattached backing of 4.5mm thick fibre reinforced cement board.

Each test specimen was clamped in four places.

Specimens tended to flash before ignition. Ignition was based on the occurance of a single flash of flame which lasted longer than 10 seconds.

187333 40122 Page 2 of 2

Australian Wool Testing Authority Ltd Copyright - All Rights Reserved



Accredited for compliance with ISO/IEC 17025 - Testing - Chemical Testing

Mechanical Testing

Performance & Approvals Testing

: Accreditation No Accreditation No

· Accreditation No. 1356

983

Samples and their identifying descriptions have been provided by the client unless otherwise stated. AWTA Ltd makes no warranty, implied or otherwise, as to the source of the tested samples. The above test results relate only to the sample or samples tested. This document shall not be reproduced except in full and shall be rendered void if amended or altered. This document, the names AWTA Product Testing and AWTA Ltd may be used in advertising providing the content and format of the advertisement have been approved by the Managing Director of AWTA Ltd.





A. JACKSON B.Sc.(Hons)